

06 General accessories

ALMEMO® memory connector with micro-SD ZA 1904 SD

02/2024 • We reserve the right to make technical changes.



- for ALMEMO® data loggers, as of version 6
- Large memory
- High data security
- Measured values can be saved to a text file.
- The memory card in the data logger can be replaced quickly and easily on site.
- Files can be transferred to a PC quickly and easily via a card reader

Technical data

Measuring instruments	for ALMEMO® 202-S, 204, 710, 809, 1020, 1030, 1033, 1036, 2470-2S, 2590-2A/-4AS, 2690, 2890, 4390, 5690, 8036, 8590, 8690 Memory connector on device output socket A2	Measured values	With 512 MB approx. 30 million measured values
ALMEMO® memory connector	Integrate drive for micro-SD card	Ring memory	no
Memory card	MicroSD industry standard (Industrial Grade SSD SLC Technology) with high performance, reliability and durability, possible up to 2 GB, standard FAT16 format	File format	ASCII text file, measured values in table format, separated by semi-colons
		Reading device	USB card reader for removable storage media
		Measuring software	WinControl (as of version 6), see Chapter Software

Variants

ALMEMO® memory connector with micro-SD memory card (1 GB) including USB card reader
Micro-SD memory card (1 GB as replacement)

Order no.
ZA1904SD
ZB1904SD



Micro-SD memory card (as replacement)